

# **Cryptanalysis of Noel McCullagh and Paulo S. L. M.**

## **Barreto's two-party identity-based key agreement**

Guohong Xie  
School of Mathematics,  
Peking University, People's Republic of China  
xgh@pku.edu.cn

### **Abstract**

Recently, Noel McCullagh and Paulo S. L. M. Barreto proposed a two-party identity-based key agreement protocol, which can be used in either escrowed or escrowless mode[1]. They also described conditions under which users of different Key Generation Centres can agree on a shared secret key. In this paper, we show that these two protocols are insecure against the key compromise impersonate attack.

**Keywords:** Cryptanalysis, Weil Pairing, ID-based, Key Agreement, Authentication

### **1 Introduction**

Traditionally, asymmetric cryptographic schemes are based on either the discrete logarithm problem or the factoring problem. The most concerned issue in implementation of cryptographic schemes is the computation cost of modular exponentiation. To overcome such a problem, the elliptic curve cryptography becomes a good choice because it reduces the computation cost while remaining the same security level. It is noticed that the decision of Diffie-Hellman is regarded as a hard problem in discrete logarithm, however, it is not a hard problem in elliptic curve cryptography due to Weil/Tate pairing. Weil/Tate pairing is a new primitive and is interesting to cryptography societies. Several cryptographic schemes are designed based on the Weil pairing, and enjoy the convenience of the property of Weil/Tate pairing. For a sound key exchange protocol, Wilson and Menezes defined several desirable security attributes[2]. We show these attributes in the following. Here we assume A and B are two honest entities.

#### **A: Known-Key Security**

In each round of key agreement protocol, A and B should generate a unique

secret key. Each key generated in one protocol round is independent and should not be exposed if other secret keys are compromised.

### **B: Forward Secrecy**

The Forward Secrecy property is that if A and B's secret keys are compromised, the session keys used in the past should not be recovered.

### **C: Key-Compromise Impersonation**

A protocol which is secure against the key compromise impersonation attack means that if A's secret key is compromised, the adversary who knows the value can not impersonate others to A.

### **D. Unknown Key-Share**

After the protocol, A ends up believing he shares a key with B, and B mistakenly believes that the key is instead shared with an adversary. Therefore, a sound authenticated key agreement protocol should prevent the unknown key-share situation.

In this paper, we show Noel McCullagh and Paulo S. L. M. Barreto's protocols are insecure against the key-compromise impersonation attack. The rest of this paper is organized in the following. In Section 2, we briefly review Noel McCullagh and Paulo S. L. M. Barreto's two part key agreement protocol from Weil/Tate pairing and show its insecurity. In Section 3, we proposed a scheme to prevent the protocol from the key compromise impersonation attack and conclude this paper..

## **2.Noel McCullagh and Paulo S. L. M. Barreto's protocol**

### **(1) An Authenticated Key Agreement With Escrow**

as with all other identity-based cryptosystems there existence of a trusted Key Generation Centre (KGC) that is responsible for the creation and secure distribution of users private keys. This agreement algorithm usesthemodified Tate pairing.

Setup:

The KGC randomly generates a master secret  $s$ , and picks a group  $G_0$  of order  $q$ . The KGC calculates  $sP$ , for some publicly known group generator point  $P$ . The KGC makes public the points  $P$  and  $sP$ , and the group  $G_0$ .

Extract:

The KGC checks that a user has a claim to a particular online Identifier.If they do, the KGC generates their private key and communicates it privately to them. Let Alice's online identifier be  $a \in \mathbb{Z}_q^*$ , possibly obtained as the hash of

an arbitrary string. Alice's public key is  $A_{pub} = (a + s)P$ , which can be computed as  $aP + sP$ . The KGC computes Alice's private key as  $A_{pri} = (a + s)^{-1}P$ .

Key Agreement:

Assume that Alice and Bob have private keys issued by the same KGC, respectively  $A_{pri}$  and  $B_{pri}$ . Alice and Bob each generate one unique random nonce  $x, y \in_r \mathbb{Z}_q^*$ , respectively. Alice compute  $A_{KA} = x(bP + sP)$ , and send  $A_{KA}$  to Bob, and Bob compute  $B_{KA} = y(aP + sP)$  and send it to Alice. After received  $A_{KA}$  and  $B_{KA}$  respectively, Alice compute  $key_A = \hat{t}(B_{KA}, A_{pri})^x = \hat{t}(P, P)^{xy}$ . And Bob compute  $key_B = \hat{t}(A_{KA}, B_{pri})^y = \hat{t}(P, P)^{xy}$ . so Alice and Bob share the same value  $key = key_A = key_B$  as their session key.

Alice		Bob
$A_{KA} = x(bP + sP)$	----->	
	<-----	$B_{KA} = y(aP + sP)$
$key_A = \hat{t}(B_{KA}, A_{pri})^x$		$key_B = \hat{t}(A_{KA}, B_{pri})^y$

This scheme is consistent because:

$$key_A = \hat{t}(B_{KA}, A_{pri})^x = \hat{t}(P, P)^{xy} = \hat{t}(A_{KA}, B_{pri})^y = key_B.$$

The escrow property derives from the KGC's ability to recover the shared session key by computing:

$$xP = (s + b)^{-1}A_{KA}, \quad yP = (s + a)^{-1}B_{KA},$$

$$key = \hat{t}(xP, yP).$$

The scheme is role symmetric, with each party performing the same operations and thus incurring the same computational cost.

## (2) An Authenticated Key Agreement Without Escrow

The key agreement without escrow differs only slightly from the algorithm given above. Again there are three algorithms, Setup, Extract and Key Agreement. This key agreement protocol uses the conventional Tate pairing, not the modified Tate pairing as the escrowed scheme.

Setup:

The KGC randomly generates a random master secret  $s$ , and picks two groups,  $G_0$  a group of order  $r$  in the base field and  $G_1$ , the trace zero group in the largest extension field, again of order  $q$ . The KGC calculates  $sP$ , for some publicly known group generator point  $P$  of the group  $G_0$ . The KGC makes public the points  $P$  and  $sP$ , and the two groups  $G_0$  and  $G_1$ .

Extract:

The KGC checks that a user has a claim to a particular online identifier. If they do, the KGC generates their private key and communicates it privately to them. Let Alice's online identifier be  $a \in_r \mathbb{Z}_q^*$ , possibly obtained as the hash of

an arbitrary string. Alice's public key is  $(a + s)P$ , which can be computed as  $aP + sP$ . Alice's private key is generated as  $(a + s)^{-1}Q$ , where  $Q$  is a generator point in the group  $G1$ . It is important that the discrete logarithm between  $(P)$  and  $Q$  is unknown<sup>3</sup>. This can be achieved by obtaining  $P$  and  $Q$  as the output of random oracles  $H1 : \{0, 1\}^* \rightarrow G1$  and  $H2 : \{0, 1\}^* \rightarrow G2$  evaluated on publicly known constant strings.

Key Agreement:

Assume that Alice and Bob have private keys issued by the same KGC, respectively  $Apri$  and  $Bpri$ . Alice and Bob each generate one unique random nonce  $x, y \in_r Z_q^*$ , respectively.

Alice	Bob
$A_{KA} = x(bP + sP)$	$B_{KA} = y(aP + sP)$
$key_A = \hat{t}(B_{KA}, Apri)^x$	$key_B = \hat{t}(A_{KA}, Bpri)^y$

This scheme is consistent because:

$$Key_A = \hat{t}(B_{KA}, Apri)^x = \hat{t}(P, Q)^{xy} = \hat{t}(A_{KA}, Bpri)^y = key_B.$$

We also note that, although the KGC has the ability to generate the private keys of both users in the protocol, it is not able to obtain the shared session key for any particular run of the protocol. The KGC can, in this instance, easily compute  $\hat{t}(P, Q)^x$  and  $\hat{t}(P, Q)^y$ , but calculating the key from these values involves solving the Computational Diffie - Hellman Problem (CDHP) over the group  $G2$ .

### (3) Key Agreement Between Members of Distinct Domains

For key agreement to be possible between members of different groups all that is needed is for the points  $P, Q$  (or just  $P$  in the case of the escrow enabled system) and the curve description to be the same (standardised). Once these group generator points and curves have been agreed upon, each KGC can generate their own random master secret. Alice's private key is generated by KGC1 with a master secret  $s1$ . Bob's private key is generated by KGC2 with a master secret  $s2$ . Alice's public key is  $(a+s1)P$  and her private key is  $Apri = (a+s1)^{-1}P$ . Likewise, Bob's public key is  $(b + s2)P$  and his private key is  $Bpri = (b + s2)^{-1}P$ . Notice that now Alice must obtain the point  $s2P$  as issued by Bob's KGC and vice-versa. Alice and Bob now perform the authenticated key agreement:

Alice	Bob
-------	-----

$$\begin{array}{ccc}
 A_{KA} = x(bP + s2P) & \text{-----}> & \\
 & & <----- & B_{KA} = y(aP + s2P) \\
 \text{key}_A = \hat{t}(B_{KA}, \text{Apri})^x & & \text{key}_B = \hat{t}(A_{KA}, \text{Bpri})^y
 \end{array}$$

This scheme is consistent because:

$$\text{Key}_A = \hat{t}(B_{KA}, \text{Apri})^x = \hat{t}(P, P)^{xy} = \hat{t}(A_{KA}, \text{Bpri})^{xy} = \text{key}_B.$$

### 3.Key compromise impersonation attack on Noel McCullagh and Paulo S. L. M. Barreto's protocol

In this subsection, we give the following scenario to show that Noel McCullagh and Paulo S. L. M. Barreto's protocol is insecure against the key compromise impersonation attack. We now take a look how the attack apply to the protocol with escrow. That is an adversary Adv who knows A's secret key can impersonate B to A.

First, the adversary Adv selects a random number y and computes  $B_{KA} = y(b+s)P$ , Next, Adv sends  $B_{KA}$  to A.  $\text{Adv} \rightarrow A : B_{KA}$ . A selects a random number a and compute  $A_{KA} = x(b+s)P$ , and send it to Adv who A thinks as B. Upon the received messages, A computes the session key KA:  $\text{key}_A = \hat{e}(B_{KA}, \text{Apri})^x = \hat{e}(y(b+s)P, x(a+s)^{-1}P)$ , and Adv computes the session key  $\text{key}_B = \hat{e}(A_{KA}, \text{Apri})^y = \hat{e}(x(b+s)P, (a+s)^{-1}P)^y = \hat{e}(y(b+s)P, x(a+s)^{-1}P) = \text{key}_A$ .

Namely, with the knowledge of A's secret key a, Adv can impersonate B to A. From Above we can know that the attack can apply not only the protocol with escrow but also the protocol without escrow and the protocol with different KGC.

To prevent this attack we modify the protocol with a signature from the idea of K.C. Reddy<sup>1</sup> and Divya Nalla<sup>2</sup>'s scheme[3].

The scheme is as follows:

Alice	Bob
$  \begin{array}{l}  A_{KA} = x(bP + sP) \\  S_A = \text{hash}(A_{KA}) \text{Apri} + x\text{Apri} \\  (A_{KA}, S_A) \quad \text{-----}>  \end{array}  $	$  \begin{array}{l}  B_{KA} = y(aP + sP) \\  S_B = \text{hash}(B_{KA}) \text{Bpri} + x\text{Bpri} \\  (B_{KA}, S_B) \quad <-----  \end{array}  $

Having received  $(B_{KA}, S_B)$ , A verifies  $\hat{e}(S_B, \text{Bpub}) = \hat{e}(\text{hash}(B_{KA})P, P) \hat{e}(B_{KA}, \text{Apri})$ . If the equation holds, then A computes

$$\text{key}_A = \hat{t}(B_{KA}, \text{Apri})^x.$$

B verifies  $\hat{e}(S_A, A_{pub}) = \hat{e}(\text{hash}(A_{KA})P, P) \hat{e}(A_{KA}, B_{pri})$ . If the equation holds, then B computes

$$\text{key}_b = \hat{t}(A_{KA}, B_{pri})^y$$

where  $A_{pub} = (a+s)P$  from  $aP+sP$  and  $B_{pub} = (b+s)P$  from  $bP+sP$ .

$$\begin{aligned} \hat{e}(S_A, A_{pub}) &= \hat{e}(\text{hash}(A_{KA})(a+s)^{-1}P + x(a+s)^{-1}P, (a+s)P) \\ &= \hat{e}(\text{hash}(A_{KA})P, P) \hat{e}(x(a+s)^{-1}P, (a+s)P) \\ &= \hat{e}(\text{hash}(A_{KA})P, P) \hat{e}(xP, P) \\ &= \hat{e}(\text{hash}(A_{KA})P, P) \hat{e}(x(b+s)P, (b+s)^{-1}P) \\ &= \hat{e}(\text{hash}(A_{KA})P, P) \hat{e}(A_{KA}, B_{pri}), \end{aligned}$$

anyone else not knowing both of the knowledge of  $A_{pri}$  and the ephemeral key  $x$  can not make the signature  $S_A$  from  $A_{KA}$ . If an adversary  $D$  have got Alice's private key  $B_{pri}$ , he can randomly choose  $y$  to compute  $y(b+s)P$  in order to impersonate Bob to share a secret key with Alice. If he uses  $y$  to compute  $S_B$ , the equation  $\hat{e}(S_B, B_{pub}) = \hat{e}(\text{hash}(B_{KA})P, P) \hat{e}(B_{KA}, A_{pri})$  will not hold, because

$$\begin{aligned} \hat{e}(S_B, B_{pub}) &= \hat{e}(\text{hash}(B_{KA})(b+s)^{-1}P + y(b+s)^{-1}P, (b+s)P) \\ &= \hat{e}(\text{hash}(B_{KA})P, P) \hat{e}(y(b+s)^{-1}P, (b+s)P) \\ &= \hat{e}(\text{hash}(B_{KA})P, P) \hat{e}(y(b+s)P, (b+s)^{-1}P) \\ &= \hat{e}(\text{hash}(B_{KA})P, P) \hat{e}(B_{KA}, B_{pri}), \\ &\neq \hat{e}(\text{hash}(B_{KA})P, P) \hat{e}(B_{KA}, A_{pri}) \end{aligned}$$

$D$  can both satisfy the verify equation and impersonate Bob to Alice successfully unless he knows the relationship between  $A_{pri}$  and  $B_{pri}$ , but this is a CDH problem.

#### 4. Conclusion

Noel McCullagh and Paulo S. L. M. Barreto's protocol is insecure against the key compromise impersonation attack. But along with the above signature the scheme will be more secure.

#### References

- [1]. Noel McCullagh<sup>1</sup> and Paulo S. L. M. Barreto<sup>2</sup>. A New Two-Party Identity-Based Authenticated Key Agreement. Cryptology ePrint Archive, Report 2004/122, 2004. <http://eprint.iacr.org/2004/122/>.
- [2] S. B. Wilson, and A. Menezes, "Authenticated Diffie-Hellman key agreement protocols", Proceedings of the 5th Annual Workshop on Selected Areas in

Cryptography (SAC '98), Lecture Notes in Computer Science, pp. 339-361, 1999.

[3] K.C. Reddy<sup>1</sup> and Divya Nalla<sup>2</sup>. Identity Based Authenticate Group Key Agreement Protocol. Lecture Notes in Computer Science Volume 2551/2002 , Springer-Verlag Heidelberg