One Round of Transposition Ensures Target Security

TRANSPOSITION ENCRYPTION ALPHABET METHOD (TEAM) OFFERS ANY TARGET SECURITY LEVEL FOR A COMPUTATIONAL PRICE

Gideon Samid Department of Electrical Engineering and Computer Science Case Western Reserve University, Cleveland, OH BitMint, LLC Gideon@BitMint.com

Keywords: unary encoding, transposition, mathematical secrecy, trans-Vernam ciphers.

Regular Research Paper

Abstract: Encoding an arbitrary bit string, by parceling it out to randomized size subsections, encoding each subsection through a unary alphabet, thereby expressing the original string via a much larger one, which upon transposition projects up to perfect mathematical secrecy. The attraction of TEAM (Transposition Encryption Alphabet Method) is in the fact that it replaces common floating-point complex computational ciphers with the utter simplicity and speed of nothing more than one round of transposition. Also enabling decoy bits, which are recognized as noise by the intended recipient, while presenting a cryptanalytic burden on the attacker. Implemented in hardware TEAM is very battery-friendly, fitting for Internet of Things application. TEAM security is based on equivocation, which classifies it as post quantum cryptography. TEAM's efficacy may be upgraded unilaterally by the transmitter through increased use of ad-hoc, not preshared randomness.

I. INTRODUCTION

Transposition is arguably the most basic cryptographic primitive, it requires no alphabet, and it's complexity is super-exponential. It lends itself to very efficient execution in hardware, which explains its popularity in most common cryptographic protocols. Herewith we investigate the premise that it may be a sufficient operation for purpose of security. We present TEAM: Transposition Encryption Alphabet Method, s cipher based on one round of transposition for generating secrecy. The TEAM cipher is based on randomized at-will encoding of the plaintext so that its transposition will generate any desired measure of security.

A bit string b comprised of t bits, can be encoded in a format b* through a string b_v comprised of v+1 bits of

identity "0" where v is the binary value interpretation of b, associated with a string b_r , of r+1 bits of identity "0", where r represents the count of leading zeros in b.

Illustration: let b = 0001011. We write v = 11, r=3, and hence:

$$b^*$$
: $\{b_v, b_r\} = \{v+1 \text{ "0"s, } r+1 \text{ "0"}\} = \{000\ 000\ 000\ 000,\ 0000\}$

There is clear bijection between b and b*.

Let string b_1 be so encoded to $b*_1$, and b_2 so encoded to $b*_2$ only that for $b*_2$, we switch the bit identities from "0" to "1". We write:

$$b_1 = \{v_1 + 1 \text{ "0", } r_1 + 1 \text{ "0"}\}$$

$$b_2 = \{v_2 + 1 \text{ "1", } r_2 + 1 \text{ "1"}\}$$

We now express a concatenation between b_1 , and b_2 as follows:

$$b_1||b_2 = \{b_{v1}||b_{v2}, b_{r1}||b_{r2}\}$$

Illustration: let $b_1 = 00101$ and $b_2 = 0001000$. Accordingly $v_1 = 5$, $r_1 = 2$, and $v_2 = 8$, $r_2 = 3$. And thus we write:

$$b_1 = \{v_1+1 "0", r_1+1 "0"\} = \{000 000, 000\}$$

 $b_2 = \{v_2+1, r_2+1\} = \{111 111 111, 1111\}$

$$\begin{array}{llll} b_1\|b_2 = \{b_{v1}\|b_{v2},\ b_{r1}\|\ b_{r2}\} = \{000\ 000\ 111\ 111\ 111,\ 000\ 1111\} \end{array}$$

Since b_{v2} is comprised of "1"s and b_{r1} is comprised of "0"s we can concatenate without confusion:

$$b_1||b_2 = \{b_{v1}||b_{v2}, b_{r1}||b_{r2}\} = b_{v1}||b_{v2}||b_{r1}||b_{r2}$$

Similarly for a string B comprised of arbitrary number, n, of subsections: $B = b_1 || b_2 || b_n$ versus $B^* = b^* || b^* || b_1 || b_n$. For an even value of i (i=1,2,...n) the b_{vi} and b_{ri} strings of b_i will be written with "1"s while for an odd value of i b_{vi} and b_{ri} will be written with :"0"s.

We now write:

$$\mathbf{B}^* = \{\mathbf{B}^*_{\mathbf{v}} = \mathbf{b}_{\mathbf{v}1} || \mathbf{b}_{2\mathbf{v}} || \dots \mathbf{b}_{\mathbf{n}\mathbf{v}}, \ \mathbf{B}^*_{\mathbf{r}} = \mathbf{b}_{\mathbf{r}1} || \mathbf{b}_{2\mathbf{r}} || \dots \mathbf{b}_{\mathbf{n}\mathbf{r}} \}$$

Further concatenating the two strings:

$$B^* = B^*_v || B^*_r = b_{v1} || b_{v2} || \dots b_{vn} || b_{r1} || b_{r2} || \dots b_{rn}$$

In order to mark where the bits of b_{vn} end, and the bits of b_{r1} begin, it is necessary that n will be divided by 4 (n = 4 MOD 4). We shall see below that this requirement may be overcome, using the NULL entity.

We now define b_0 = 'NULL' as the 'NULL' string which will be mapped to b^*_0 with v = 0, and r = 0, namely: $b^*_0 = \{v+1 \ "0", r+1 \ "0"\} = \{0,0\}$ or: $b^*_0 = \{v+1 \ "1", r+1 \ "1"\} = \{1,1\}$ where we agree to switch bit identities for adjacent NULLs characters: $b_0b_0 = \{0,0\}\{1,1\}$, or $\{1,1\}\{0,0\}$, no $\{00\}\{0,0\}\{1,1\}\{1,1\}$.

One ready use of the NULL is to allow an arbitrary string B to be parceled out to any n number of subsections. Adding one, two, or three NULLs anywhere in B will make the total number of subsections $n'=0\ MOD\ 4$ and will insure that the bit identity comprising b_{vn} will be opposite the bit identity comprising b_{r1} so there will be no confusion as to when b_{vn} ends and b_{r1} begins.

We can implant NULL characters throughout a bit-string:

$$B = b_1 \parallel b_2 \parallel ... \parallel b_n = b_1 \parallel b_2 \parallel ... \parallel b_i \parallel b_0 \parallel b_0 \parallel b_0 \parallel b_{i+1} \parallel b_{i+2} ... \parallel b_n$$

and so:

$$B^* = b^*_1 \parallel b^*_2 \parallel ... \parallel b^*_n = b^*_1 \parallel b^*_2 \parallel \parallel b^*_i \parallel b^*_0 \parallel b^*_0 ... \parallel b^*_0 \parallel b^*_{i+1} \parallel b^*_{i+2} \parallel b^*_n$$

We shall regard the above described encoding of an arbitrary bit string as TEAM-encoding, and the reverse process as TEAM-decoding.

Let B^{*T} be an arbitrary transposition of B^* using a transposition key, K^T : $B^{*T} = TP$ (B^* , K^T), and let $|B^*| = |B^{*T}|$ be the bit count of either of these two strings.

Both B*^T, and B* have the same number of '0' bits, 0_c , and the same number of '1' bits, 1_c where $0_c + 1_c = |B^*| = |B^*|$. Let bit string B' \neq B be encoded into B'* where $0'_c =$

 0_c , and $1'_c = 1_c$. Accordingly there exists a transposition key K'_t such that $B^{*T} = TP(B'^*, K'_t)$. In other words, anyone with possession of B^{*T} without a possession of its generating transposition key, K_t will not be able to determine whether B or B' were used to generate it. Since B' is arbitrary, this means that all the bit strings that can be encoded to a string with 0_c zeros and 1_c ones -- are valid candidates for being the string that was transposed to B^{*T} . The larger the class of such B' string, the larger the equivocation -- up to perfect secrecy as defined by Claude Shannon.

We shall show now how to encode an arbitrary B' to B'* with $0'_c = 0_c$, and $1'_c = 1_c$

Step 1: parcel B' to m consecutive subsections of arbitrary sizes: $b'_1 \| b'_2 \| \dots \| b'_m$.

Step 2: TEAM-encode B': Read b'_{1v} and b'_{1r} and construct $b'_1 = \{v'_1 + 1 \ "0", \ r'_1 + 1 \ "0"\}$. Continue respectively with b'_i for i=1,2,...p where $p \le m$, as follows:

$$b'_i = \{v'_i + 1 "Q", r'_i + 1 "Q"\}$$

where 'Q' represent bits of identity '0' for odd i, and identity '1' for even i.

Step 3: TEAM-Encode B' to B'*, as above, then count the number of '0' bits in B'* $(0'_c)$, and the number of '1' bits in B'* (1_c) :

$$0'_{c} = \sum v'_{2i+1} + r'_{2i+1} + 2$$
 for $i=0,1,2,3$... no higher than $p/2$. $1'_{c} = \sum v'_{2i} + r'_{2i} + 2$ for $i=1,2,...$ no higher than $p/2$.

If $0'_c > 0_c$, or $1'_c > 1_c$ then B' go to "oversize options". Otherwise:

Step 4: compute:

$$\Delta 0 = 0_{c} - 0'_{c}$$

 $\Delta 1 = 1_{c} - 1'_{c}$

Add $\Delta 0$ '0' bits as a header according to the set forth "header protocol", and add $\Delta 1$ '1' bits as a trailer according to the set forth "trailer protocol.". The resultant header and trailer wrapped string B'* \rightarrow B'*_w is comprised of 0_c bits of identity '0' and 1_c bits of identity '1', and hence B'*_w is a permutation of both B* and B*^T. Namely, there exists a transposition key K'_t such that:

$$B^{*T} = TP (B'^{*}_{w}, K'_{t})$$

Hence anyone holding B*^T without holding K_t cannot conclude that B*^T was generated from B*, and not from B'*. Every bit string sufficiently short will qualify as B' in the

preceding analysis. This includes B' comprised of a string of 'NULLS'. In other words the size of B*, |B*|, and its Hamming weight, not its content, determines the range of candidate strings (B') that all qualify to be the string that generates B*^T. It is this vastness of this range that determines the security of the cipher.

When we combine this fact with the ability of the TEAM cipher user to increase the size of the TEAMencoded version, (B*), of the original string B, at will (using as many NULL elements as desired, as well as wrapping the B with header and trailer as described ahead), we conclude that a transmitter of a message B using the TEAM cipher would be able to increase indefinitely the range of plaintext candidates that would encrypt to the transmitted ciphertext (B*). This is a very strong statement. Which in effect makes it unnecessary to use any more algorithmic protection for data. Using the TEAM cipher, security is achieved through investing in greater computational effort in terms of executing transposition of large bits strings and through handling and transmitting large ciphertext. This resource investment is decided ad hoc by the user, not the cipher designer or builder. Such shift of responsibility for the security of transmitted data is far reaching.

OVERSIZE OPTIONS

In the event that $O'_c > 0_c$, or $1'_c > 1_c$, then one can try a different way to parcel out B'. Otherwise, it is possible to increase the size of B through adding NULLs or through attaching larger headers and trailers. This can be done until 0_c and 1_c are high enough, implying that the TEAM encoder has full control over the degree of equivocation that protects their transmission.

A. Header/Trailer Wrapping

The TEAM-encoded bit string B* over bit string B, may be wrapped with a leading header, HDR, and a trailing trailer TRL: $B^* \rightarrow B^*_w = HDR-B^*-TRL$.

The header will be in the form 00.....1. Namely h '0' bits followed by '1', where h=1,2,.... open ended.

The trailer will be in the form 011.. 1. Namely l '1' bits followed by '0', where l = 1,2,... open ended.

The values of h and *l* are arbitrary, and determined by the encoder.

As defined, the recipient of the wrapped string B*_w will readily strip the header and the trailer to recover the unwrapped version, B*. To strip the header the recipient will remove all the leading zeros and the following '1'. To

strip the trailer the recipient will remove all the trailing '1' and the preceding '0'.

Wrapping allows the TEAM encoder to add as many '0' and '1' bits to the pre-transposed string, in order to pack the transposed list with the same number of '1' an '0' bits, or any other ratio.

If headers and trailers are allowed then, at a minimum a single 0 added header and a single 1 added trailer will be needed to properly interpret the bit string.

B. Encoding Considerations

TEAM encoding creates an encoded string B* off a pre-encoded bit string B, such that the encoded size (bit count) is larger than the pre encoded size. We first examine this size-factoring.

It is readily seen that the smallest increase in size will happen for a string comprised of n "0" bits: 00....0. Encoded as a single section, it will register v=0, r=n. Hence: $B^* = \{1 \text{ "Q", (n+1) "Q"}\}$ where Q is a bit of either identity "1" or identity "0". Since there is only one section we may have opposite identities for the v and the r. Alternatively we could add a NULL element. and keep both the r bits and the v bits of same identity.

So if B = 000000 then $B^* = \{ 0000000, 1 \} = 00000001$ or $B^* = B^*$ NULL = 0000000101

In the first way the size of B* is $|B^*| = n + 2$, and the latter way it is $|B^*| = n + 2 + 2$. Namely $|B^*| \sim |B|$.

The largest expansion happens for a string of n bits of identity "1": B = 11.....1. In the case where the string is referred to as a single section we have $B^* = \{2^n - 1 \text{ "Q"}, 1 \text{ "Q"}\}$. An exponential expansion: $\eta = |B^*|/|B| = 2^n/n$.

The actual expansion, η , ranges between these two extremes:

$$1 \le \eta \le 2^n$$

When an n-"1" bits string B is divided to s subsections of equal size then the encoded version, B* counts: $|B^*| = s * 2^{n/s}$ bits where the size decreases with rising value of s.

To minimize the value of η for an arbitrary bit string, B, comprised of n bits, one should divide it to the maximum number of subsections: one-bit size each. We can write:

for b=0 we have v=0, r=1, and hence $b^* = \{Q, QQ\}$ and for b=1 we have v=1, r=0, and hence $b^* = \{QQ, Q\}$

where Q is a bit of either identity 1 or identity 0.

Accordingly b* is three times the size of b: $\eta = 3$

Analyzing subsections of size 2 bits:

b v r b*
----00 0 2 Q,QQQ
01 1 1 QQ,QQ
10 2 0 QQQ,Q
11 3 0 QQQQ,Q

This is average size increase of $\eta = 4.25$

for |b| = 3 the η will range from 5, (for 000, 001, 010, 011) to 9 (for 111).

C. Subsection Strategy

The strategy for parceling the plaintext B to subsections is critical in determining the size increase of the ciphertext, $B^* = B^{*T}$ over the plaintext B. We have seen above how large is this range. In practice the subsections may be of varying sizes. These size variety may be chosen through a randomization process, perhaps between two limits (upper and lower per subsection size). By using adhoc randomness the security of the operation vastly increases. Yet, it can also be chosen in some deterministic way. In fact the very choice of the subsection sizes may be used to deliver a secondary hidden message to the intended recipient.

D. Decoy Strategy

The transmitter of a TEAM message may increase security by using a high η value -- a large ciphertext compared to the un-encoded plaintext. They can use two ready methods to inflate the ciphertext, and add so called 'decoy bits'. One method is by peppering the message with NULL elements. A NULL element does not add anything to the message but it requires 2 bits to be expressed. With NULLs it is impossible to add at will more 0 bits than 1, or at will more 1 bits than 0. The alternative method is headers and trailers where both '1' bits and '0' bits can be added in any desires number.

The following string, E. is empty:

$E = 0000000000001 \ 0101010101010101010101 \ 01111111$

The transmitter may 'hide' a message M in a series of empty transmissions $E_1, E_2, ...$:

$$E_1 E_2$$
,..... $E_i M E_{i+1}$, E_{i+2}, E_q

By applying sufficient decoys the transmitter may protect his message with any desired measure of security.

II. OPERATION


The transmitter of a TEAM enciphered message enjoys a great measure of control over the security of the sent message. The transmitter decides how much to pay, aware of how much security will be purchased. The price is rated with computational burden. Some of this burden may be alleviated through hardware, and some through communication channels and memory.

TEAM security is based on a shared transposition key and a single transposition round, on encoding variety, and on decoy strategy. The larger the transposition list, the better the security. This size, depending on implementation, may be non pre-shared, namely unilaterally determined by the transmitter on account of the desired security. Same for the encoding scheme, and the decoy management, which are also unilaterally determined and feed on ad-hoc randomness. That means the transmitter who is in the best position to appreciate the security needs for its transmission, is the right agent to determine which encoding scheme to use and the degree of decoy defense. This determination may be made for each transmission. So that when a single key must be used over and over again, it can each time, be used with more protection through more elaborate encoding and more extensive decoy management. This is an important distinction relative to mainstay ciphers where security is built in to the published algorithm and is threatened by unpublished attack scheme. The TEAM user relies on adhoc high quality randomness in desired quantities. Security shifts from the algorithm designer to the message transmitter; from well known cipher algorithm to unknown on-demand randomness.

A. Unary Encoded Packaing

The figure abreast ciphertext) is wrapped by a header and a trailer. The header has 6 elements: (a). message start signal, (b) sender id, time of transmission, open fields, (c) encoding data, (d) transposition key indicators, (e) payload size, (f) header

The figure abreast shows how the payload (the hertext) is wrapped Unary/Hybrid Packaging



end indicator. The trailer is identified with four elements: (p) trailer start indicator, (q) transmission history, (r). signature (payload hash / header hash), (u). end of trailer indicator.

B. Transposition Options

We consider two methods. One is based on US Patent 10608814, Equivoe-T, the other on hard-wired TSIC (Transposition Specific Integrated Circuits). Equivoe-T offers the advantage of having an integer as a key, which applies to any size of transposed list. This gives the TEAM user the advantage of choosing each time a different size of bit string to transpose. TSIC is much faster, but it is geared towards a fixed size bit string to be transposed. We will focus on the TSIC fixed size option.

C. Fixed Size Transposition

The advantage of fixed size transposition in hardware implementation is that it allows for hard wiring of the transposition operation to allow any permutation of n-items list to any other permutation of the same list. The issue here is that this transposition is fixed, and applies to a fixed size list

Size variety can still be applied over a range from some low threshold L, and high threshold H (bit count). Any size value $X: L \leq X \leq H$ can be used for the payload, with the balance of H-X bits contributed through NULLs or through header or trailers, such that the pre-transposition size will always be H, which is the hard wired size.

It can be implemented over a fixed size input and output, of n item, where some t fixed transposition wiring units are listed in order: T₁, T₂,.... T_t. These t transposition rounds are combined into a single device. The input to the combined device includes a designation of which u transposition units (among the available t transposition operations) are to be applied over the input to generate the respective output. This list of u items is the 'secondary transposition key', K*_t. The first key is expressed in the hard-wired t units. This implies that a group can share the hard-wired device with t transposition units, but bilateral confidential communication within the group will be carried out via a secret shared secondary transposition key, which has a key space of 2^t.

Every processing round in the device may involve a randomized selection of the next K^*_t key, to be used in the next processing round in the device (the next application of the TSIC). Say the first payload P_1 is comprised of the first

message M_1 , and the secondary transposition key to be used for the next message: K^*_{t1} : $P_1 = M_1 - K^*_{t2}$. P_1 will be transposed with the pre agreed first transposition key, K^*_1 :

$$P_1^T = TP ([M_1-K^*_{t2}], K^*_{t1})$$

and then:


$$P_2^T = TP ([M_2-K_{t3}], K_{t2})$$

and so on for i=1,2,...

$$P_i^T = TP([M_i-K^*_{ti+1}], K^*_{ti})$$

There are 2^t combinations to select active units among the available t, so the key space for the secondary key is: $|K^*_{t}| = 2^t$.

The transposition can be hard wired to operate on individual bits or on substrings of bits of equal size.



Fixed Size TSIC

The device input string S_0 will enter the first hard wired transposition unit, T_1 , and come out transposed, S_1 . This output string, S_1 , will then encounter a decision node. If T_2 is listed in K^*_t as a unit to be activated then S_1 will be fed into T_2 for another round of transposition. If T_2 is not listed in K^*_t then S_1 will by pass the 2nd transposition

unit and be routed to a similar decision before node T_3 . Every transposition unit will be preceded by a routing decision junction based on the value of K^*_t .

The device will be built to allow for reverse transposition by simply reversing the input/output ports, using the same K^*_{t} .

TSIC may feature, say, n=10⁶ register bits, and t=1000 transposition units, which will allow this device to be used in 2^{1000} different ways: $|K^*_t| = 2^{1000} = 1.07 * 10^{301}$.

D. Latchable TEAM cipher

The transposition operation is the security hub of the TEAM operation. One may then implement it in a latchable device, to be bio-activated, and be latchable to a computer to provide specifically transposition and reverse transposition services only.

E. Decryption

The recipient of the ciphertext (the transposed encoded message, B^{*T}), will first reverse-transpose it, then decode it to extract the original message:

$$B^{*T} \rightarrow B^* \rightarrow B$$

F. TEAM hash

Any bit string can be parceled out to substrings, such that each substring is comprised only of same identity bits. And if the number of such substrings divides by 4 then this string can be interpreted as TEAM-encoded off a smaller string. If the total number of such substrings does not divide by four then one could concatenate to it Q, QQ, or QQQ as required: " where O is a bit of identity opposite the identity of the last bit in the string to which it is concatenated (or a similar solution). Hence if a string B is comprised of 37 strings and the last string is 111, then QQQ is needed to make the count of subsections divide by 4, namely QQQ = 010. This arbitrary string comprised of 4k same identity substrings (k=1,2,...) can be compressed to its TEAMdecoded version. The compressed encoding can be further compressed iteratively. This 'decoding' process is not reversible because the corresponding encoding involves an arbitrary division of the decoded string to substrings.

Let B_0 be the original string, of size $|B_0|l$ bits. It can be compresses (as stated above, in a lossy way) to B_1 , which in turn can be compressed (decoded) to B_2 , and so on, string B_i may be compressed to string B_{i+1} . This process may continue until a terminal string B_t comprised on NULLs. Unlike the typical hashing procedures, the TEAM hash does not end at a preset size, but it can be continued until the hash equals or is less than a threshold size. The resultant hash may be applied like the more common hash procedures.

We designate dB as the TEAM-decoded version of string B. And so we can write: $B_i = dB_{i-1} = d^jB_{i-j} = d^iB_0$.

Illustration: Let $B_0 = 11100110010001$. B_0 is comprised of 7 same-bit-identity strings: 111 00 11 00 1 000 1. We need therefore to concatenate it with Q=0:

$$B'_0 = 111\ 00\ 11\ 00\ 1\ 000\ 1\ 0$$

So $dB' = b_1 || b_2 || b_3 || b_4$, where:

$$\begin{aligned} b_1 &= (v_1 = 2, \, r_1 = 0) = 10 \\ b_2 &= (v_2 = 1, \, r_2 = 2) = 001 \\ b_3 &= (v_3 = 1, \, r_3 = 0) = 1 \\ b_4 &= (v_4 = 1, \, r_4 = 0) = 1 \end{aligned}$$

Thus:

$$dB' = b_1 || b_2 || b_3 || b_4 = 10\ 001\ 1\ 1$$

The original string is comprised of 14 bits, and the decoded one is comprised of 7 bits.

Decoding again: dB' = 1 000 111 is comprised of 3 same-bit-identity subsections, so Q=0 will have to be added to create a number of subsections that divides by 4:

$$d(dB')' = d(1\ 000\ 111\ 0) = b_1 \parallel b_2$$

$$b_1 = (v_1 = 0, r_1 = 2) = 00$$

 $b_2 = (v_2 = 2, r_2 = 0) = 10$

And hence:

$$d(dB')' = d(1\ 000\ 111\ 0) = b_1 \parallel b_2 = 0010$$

To continue we need to add '1', and end up with a string with four subsections

$$d(d(dB')')' = d(00\ 1\ 0\ 1) = b_1 \parallel b_2$$

$$b_1 = (v_1 = 1, r_1 = 0) = 1$$

 $b_2 = (v_2 = 0, r_2 = 0) = NULL$

and hence:

$$d(d(dB')')' = d(00\ 1\ 0\ 1) = b_1 \parallel b_2 = 1$$

To continue, we must add QQQ = 010

$$d(d(d(dB')')')''' = d(1010) = b_1 \parallel b_2$$

$$b_1 = (v_1 = 0, r_1 = 0) = NULL$$

 $b_2 = (v_2 = 0, r_2 = 0) = NULL$

G. Transposed HASH

Any string in the series B_0 , B_1 , may be transposed before it is decoded. When these transpositions are carried out with a secret key, they create a secret hash.

We write:
$$B_i = H(B_{i-1}, K_t) = HB_{i-1}$$
 for $i=1,2,...$

H. Implementation

TEAM can be used generically wherever symmetric encryption is used. But it would be prominent for applications based on a latchable gadget fitted into a computer, and holding the TSIC chip. A similar chip will be useful for medical devices that are body implanted and are fine-tuned remotely. It is important to insure that these devices will not be mal-controlled. Alas, same devices use tiny battery and can't spare the energy to compute AES or alike.


I. TEAM Security

While common ciphertexts commit to their generating plaintext, and given enough cryptanalysis will yield their secret, a TEAM cipher will challenge its attacker with irreducible equivocation, the extent of which is determined by its user. This is a strong security statement.

We have seen that given a plaintext P, the transmitter thereto will be able to render an arbitrary different plaintext, $P' \neq P$ to be an equally likely candidate for the generating plaintext. To do so, the transmitter may have to inflate the number of transposable zeros (0_c) and the number of transposable 1 bits (1_c) to a sufficient level. From a practical point of view this feature is equivalent to mathematical secrecy as defined by Claude Shannon.

TEAM cipher equivocation security may be extended to repeat use of the same transposition key. Let a transmitter use the same transposition key, K_t , over q plaintext messages P_1 , P_2 , P_q . For each transmission i (i=1,2,...q) let an attacker have a list L_i of plausible plaintexts for that transmission, where this list is compiled before the respective ciphertext is released. So a-priori the number of possible sets of q messages is: $EQV = \pi |L_i|$. Since the transmitter can inflate the size of the pre-transposed string to any desired size, they can assure that given the q released ciphertext, there are likely to remain some desired number s,

of transposition keys that will reduce the equivocation lists L_1 , L_2 , L_q to L'_1 , L'_2 ,..... L_q , respectively where while for every i=1,2,...q there exists $L'_i < L_i$, the residual equivocation EQV'(s) = π $|L'_i|$ will be above a preset security threshold, S: EQV'(s) < S. In practice this implies that the user can control the security projection of their transmitted data.



Buying Security with Processing Effort

J. Outlook

In the post-Coronavirus universe we expect to experience a proliferation of work-from-home practice. Bankers and confidential workers of all sorts will find it necessary to routinely communicate highly confidential data among distributed locations. This will pose new challenges before cyber technology. Security responsibility will have to shift to the transmitters of sensitive information. Not only content, but pattern will have to be concealed to enable the emerging, lasting work configurations. The new wave of Trans Vernam ciphers is well prepared to meet that challenge, and the TEAM cipher fits right in.

III. REFERENCE

- 1. US Patent 10,608,814 Equivoe-T: Transposition Equivocation Cryptography
- 2. US Patent 10,523,642 Skeleton Network
- Samid "Randomness Rising The Decisive Resource in the Emerging Cyber Reality" 14th International Conference on Foundations of Computer Science (FCS'2018, Las Vegas, USA)
- Samid "Shannon's Proof of Vernam Unbreakability" https://www.youtube.com/watch?v=cVsLW1WddVI
- 5. Shannon 1949: "Communication Theory of Secrecy Systems"
 - http://netlab.cs.ucla.edu/wiki/files/shannon1949.pdf
- 6. Smart: "Cryptography Made Simple", Springer.
- 7. Vernam, US Patent 1310719, 13 September 1918.
- 8. Williams 2002: "Introduction to Cryptography" Stallings Williams, http://williamstallings.com/Extras/Security-Notes/lectures/classical.html